

Fold Stream







Folding & Gluing Reinvented -Bespoke, Thrilling and Unique

The multi-transport-belt concept of the Folding & Gluing machine Fold Stream enables a user-friendly setup for various applications on the plough-fold unit. With this unique concept, there is no need to adjust the belts for a changeover when producing digital and offset-printed products. The guided toolings with quick-release locks allow straightforward positioning. Adjustable springloaded drive-rollers guarantee optimum and even downward pressure on the product. For a smooth turnover of the flaps, all ploughs can easily adjust in height & angle for precise folding. An interactive touch-screen controls the machine's speed and glue applications in various positions and lengths.

Complementary Equipment

continous feeder
batch counter
second gluing head
tipper plate
turning unit
side lay
tape applicator
shingle delivery unit

Applications

presentation folders, ticket sleeves, envelopes, pouch boxes, mailers, greeting cards, folding plans, promotional articles, folding games, pillow boxes, wallets, pocket folders, gable boxes, tape applications

paper weight	$180 \text{ up to } 400 \text{ g/m}^2$
blank width	60 up to 520 mm
blank length	60 up to 450 mm
machine speed; adjustable*	2 to 50 m/min
electrical consumption	3,5 kW
electric connection	230 V/single phase/50 Hz/60 Hz
pneumatic connection	6 bar/5 L/min

^{*}The actual production speed and effective net performance depend on the format, style, and composition of products, the paper quality and the quality of the die-cut and greased blanks, and the general production conditions.



Lookbook

